


































BASESTATION 1000

vs.

Hunter® ACC

Features	BASESTATION 1000	Hunter® ACC	Rain Bird® LXD/LXME
Easy to use			
TDT Soil Moisture Sensor-Based Watering			
Free Ethernet Port			
Flow Management, Monitoring, & Reporting			
Cloud-Based Central Control			
Simultaneous Two-Wire & Conventional Wire			
LiveView™			
Search for, Assign, & Reassign Stations from the Controller			
Controller Level 3 Tier Security Passcodes			
On-Screen Help			

Hunter and ACC are registered Trademarks of Hunter Industries. Rain Bird, LXD, & LXME are registered Trademarks of Rain Bird Corporation

 Feature is available
  Feature is limited
  Feature is not available

BASE·LINE
IRRIGATION SOLUTIONS™



The BaseStation 1000™ is the newest addition to Baseline's family of intelligent irrigation controllers. It is easier to use and program than any other controller on the market and yet it still provides you the essentials of intelligent irrigation management, including Baseline's patented soil moisture technology and powerful central control and mobile device compatibility that will save you time, money, and water.

Specification	BASESTATION 1000	Hunter® ACC	Hunter® I-Core	Rain Bird® LXD/LXME	Toro® TDC
Conventional Wire Configurations	12 - 48	12-42	6-42	LXME: 8-48	N/A
Conventional Wire Expansion Module Count	12	6	6	LXME: 4, 8, 12	N/A
Maximum Two-Wire Zone Count	100	99	42	LXD: 200	200
Simultaneous Two-wire & Conventional Wire	Yes	No	Yes	No	No
Number of Programs	20-40	6	4	4	10
Start Times per Program	8	10	8	8	6
Recommended Smart Watering Method	Up to 20 biSensors™ Moisture Sensors	Solar Sync™	Solar Sync™	ET Manager™	Rain Sensor
Number of Master Valves Supported	1-3	0-2	1- NC Only	LXME: 1, LXD: 5	6
Number of Flow Sensors Supported	1-3	1	1	LXME: 1, LXD: 5	N/A
Real-time Flow Monitoring & Management	Yes	Yes	No	Yes	No
Flow Fault Shutdown Report & Alert	Yes	Yes	Yes	Yes	No
Learn Flow by Zone	Yes	Yes	No	Yes	No
Maximum number of Pause Devices	4 + biSensors™	4	3	LXME: 1, LXD: 4	-
Central Control Compatible	Yes	Yes	No	Yes	Yes
Control with Mobile Phones & Tablets	Yes	No	No	No	No
Free Built-in Ethernet Port	Yes	No	No	No	No
Configurable Water Windows	Each Hour Configurable By Program	Start & End Time By Program	Start & End Time By Program	Start & End Time By Program	-
Soak Cycling	Intelligent Soak Cycling™	Yes	Yes	Yes	No
Stop Program based on Switch or Sensor	Yes	Yes	Yes	Yes	No
Pause Program based on Switch or Sensor	Yes	Yes	Yes	Yes	No
Start Program based on Switch or Sensor	Yes	No	No	No	No
Maximum Simultaneous Stations	15	6	5	LXME: 5, LXD: 8	20
On-Screen Help Text	Yes	Limited	No	LXME: No LXD: Prompts	No
English & Spanish	Yes	Yes	Yes	Yes	No
Nonvolatile Memory	Yes	Yes	Yes	Yes	Yes
Programming Backup for off site storage	USB & Internet	No	No	Module	None
Software Update	USB & Internet	With Computer	With Computer	Through IQ	-
Controller Security (Pin Code) Protection	3 Tier	No	No	No	No
Solenoid Current & Voltage Test & Report	Yes	No	No	No	No

Hunter, ACC, I-Core, & Solar Sync are registered Trademarks of Hunter Industries. Rain Bird, LXD, LXME, & ET Manager are registered Trademarks of Rain Bird Corporation. Toro and TDC are registered Trademarks of the Toro Company

rev 05162012