



- ① VALVE AND PIPING PER PLANS
- ② MOISTURE-RESISTANT CONNECTION TO VALVE (DBR/Y-6 OR EQ.)
- ③ MOISTURE-RESISTANT CONNECTION FOR COMMON WIRE TO VALVE (DBR/Y-6 OR EQ.)
- ④ TWO-WIRE - GAUGE PER PLANS
- ⑤ POROUS MATERIAL FOR DRAINAGE - 3" MINIMUM
- ⑥ MAINLINE AS PER PLANS
- ⑦ TWO-WIRE RED TO RED *biCODER* MOISTURE-RESISTANT CONNECTION (DBR/Y-6 OR EQ.)
- ⑧ TWO-WIRE BLACK TO *biCODER* BLACK MOISTURE-RESISTANT CONNECTION (DBR/Y-6 OR EQ.)
- ⑨ BASELINE BL-5201 VALVE *biCODER* - ATTACH TO VALVE BOX WITH TIE OR METAL SCREW
- ⑩ CORNER VALVE BOX SUPPORT (TYPICAL OF FOUR)

NOTE: MOISTURE-RESISTANT CONNECTORS 3M DBR/Y-6 OR EQUAL TO BE INSTALLED IN VERTICAL POSITION AS SHOWN.

# BASELINE BL-5201 SINGLE STATION VALVE BICODER NTS